



QUALITY... PLAIN & SIMPLE®

## Ford AOD Hi-Tech Kickdown Kit Part# KD-2AODHT

# Ford AOD Hi-Tech Kickdown Kit

Part# KD-2AODHT

**Building American Quality... With A Lifetime Warranty!**

10924 Murdock Dr. • Knoxville, TN 37932 • (865) 966-2269 • FAX (865) 671-1999 • tech@lokar.com • www.lokar.com

### **General Installation Notes:**

Please read instructions completely before beginning installation. If you have any questions please do not hesitate to call.

**NOTE:** Do not attempt to install kickdown kit while engine is running. Be sure engine, body and frame are grounded properly.

You may want to use Lokar's Stainless Steel Carburetor Bracket and Springs (Part # SRK-4000) to mount your kickdown.

We recommend using an anti-seize lubricant on all aluminum threads before installation! Do not over tighten while fitting cables.

Cut housing by using diagonal cutters, Lineman pliers, or taping and using a fine-toothed hacksaw. Klein Side Cutters, Part # D2000-28 (available at Grainger's, Part # 4A838) work best.

Contact OTC at 1-800-533-5338 for T.V. Cable Gauge #T86L-70332A or Rotunda #307-152

### **Ford AOD Kickdown Kit Installation**

**Step 1:** Install transmission cable bracket onto the second trans pan bolt behind the gearshift lever. **Fig. 1**

Cable actuated floor shift: Install the cable, attaching bracket to the transmission bell housing mounting boss. **Fig. 2**

**Step 2:** Install T.V. lever onto threaded T.V. shaft in the center of trans shift lever. **Fig. 1**


**Step 3:** Install the swaged end of cable housing into trans bracket. (*installed in Step 1*)

**Step 4:** Install Lokar carburetor bracket and springs (Part # SRK-4000) onto driver's side rear stud of carburetor. Bolt kickdown adjuster bracket supplied with kickdown kit onto carburetor bracket using bolt and Nylock nut supplied with kickdown kit. (If not using Lokar Part # SRK-4000, mount parallel to valve cover to bottom hole on carb linkage). **Fig. 3**

**Step 5:** Install hex carb fitting with Lokar Cable Slide into lowest 1/4" hole on carb arm. Tighten hex carb fitting completely.

**Step 6:** Route cable housing up to kickdown adjuster. Mark cable housing for cut, adding 1" for slack. Be sure to remove inner wire before cutting!

**Step 7:** Install cable housing ferrule. Slide ferrule back up to the end of cable housing and slip into kickdown adjuster. Install inner cable by starting at trans arm. Feed through trans arm, spring, and housing up to carb, through Lokar Cable Slide Fitting, and into kickdown end-stop. With carb at idle, slide end-stop up to gray clip and lightly tighten setscrew with Allen wrench supplied in kit.



**Fig. 1**

Trans Arm

*Continued on back...*



QUALITY... PLAIN & SIMPLE®

## Ford AOD Hi-Tech Kickdown Kit Part# KD-2AODHT

**Pressure adjustment instructions for use with a factory Ford pressure gauge or equivalent. (Not sold or supplied by Lokar)**


**Step 8:** Attach T.V. Pressure Gauge with Hose to the T.V. port on the transmission. Use (0-60 psi) oil pressure gauge, or OTC tool #T86L-70002-A or equivalent.

Note: If service tool is not available, in order to avoid the exhaust system, obtain the following locally available material.

- One 1/8-inch NPT Female Hansen Fitting.
- One 1/8-inch NPT Male Hansen Fitting.
- One 1/4-inch NPT 90 degree elbow connector.
- One high-pressure hose fitting.

The pressure gauge should have 200mm (8 feet) of flexible hose to make the gauge accessible while operating the engine.

**Fig. 2**



...Continued from front

# Ford AOD Hi-Tech Kickdown Kit

Part# KD-2AODHT

**Building American Quality... With A Lifetime Warranty!**

10924 Murdock Dr. • Knoxville, TN 37932 • (865) 966-2269 • FAX (865) 671-1999 • tech@lokar.com • www.lokar.com

**Step 9:** Insert tapered end of the T.V. Cable Gauge OTC #T86L-70332A or Rotunda #307-152 between the kickdown end-stop on the end of the cable and hexcarb fitting and Lokar Cable Slide that attaches to the throttle lever. Push the T.V. Gauge Tool, forcing the aluminum kickdown end-stop away from the hexcarb fitting. Make sure gauge block is pushed in as far as it will go. (Telephone number is 1-800-533-5338 for OTC and you may order the tool direct from them.)

**Step 10:** Operate engine until reaching normal operating temperature. The transmission fluid temperature should be approximately 38°-70° C (100°-150° F). Do not make pressure check if transmission fluid is cold or too hot to touch.

**Step 11:** Set parking brake and place shift selector in NEUTRAL. With gauge tool in place and engine idling in NEUTRAL, the T.V. pressure should be (35 psi) using the following procedure.

**Note: Do not check or set TV pressure in PARK.**

**Step 12:** Make major adjustments by sliding the kickdown end-stop and pulling inner wire tighter, loosen setscrew with the wrench supplied, make your major adjustments, and then tighten screw. Make minor adjustments at the two nuts on the kickdown adjuster.

**Step 13:** When finished with all adjustments, remove the T.V. cable gauge tool.

**Step 14:** Remove gauge tool, allowing cable to return to its normal idle position. With engine still idling in NEUTRAL, T.V. pressure must be at or near zero. If not, reinstall gauge block. Repeat steps 9 through 12 but set T.V. pressure to a pressure less than (35 psi) but not less than (30 psi). Remove gauge block and recheck T.V. pressure to determine if it is at or near zero.

**Fig. 3**

